

## Torquer Locking Well Plugs Size Specification guide

<u>PIPE SIZE</u>	<u>PART #</u>	<u>DESCRIPTION</u>	<u>MIN SIZE</u>	<u>MAX SIZE</u>
* 1/2"	T.5	1/2" Torquer	.500" (12.5mm)	.725" (18.5mm)
3/4"	T.75	3/4" Torquer	.750" (19mm)	1.100" (28mm)
3/4" 80	T.75-80	3/4" Torquer	.680" (17mm)	.950" (24mm)
* 1"	T1	1" Torquer	.925" (23.5mm)	1.260" (32mm)
* 1.25"	T1.25	1 1/4" Torquer	1.220" (31mm)	1.620" (41mm)
* 1 1/2"	T1.5	1 1/2" Torquer	1.450" (37mm)	1.870" (48mm)
2"	T2	2" Torquer	1.990" (50mm)	2.460" (62.5mm)
2" - 80	T2-80	2" Torquer	1.865" (47.5mm)	2.340" (59mm)
* 2 1/2"	T2.5	2 1/2" Torquer	2.290" (58mm)	2.800" (71mm)
* 3"	T3	3" Torquer	2.830" (72mm)	3.400" (86.5mm)
3 1/2"	T3.5	3 1/2" Torquer	3.400" (86mm)	3.750" (95mm)
4"	T4	4" Torquer	3.985" (98mm)	4.400" (112mm)
4 1/2"	T4.5	4 1/2" Torquer	4.400" (112mm)	4.750" (121mm)
4" - 80	T4-80	4" Torquer	3.700" (94mm)	4.125" (105mm)
* 5"	T5	5" Torquer	4.700" (119mm)	5.125" (132mm)
5 1/2"	T5.5	5 1/2" Torquer	5.400" (137mm)	5.750" (146mm)
6"	T6	6" Torquer	5.725" (145mm)	6.350" (162mm)
6 1/2"	T6.5	6 1/2" Torquer	6.400" (163mm)	6.750" (171mm)
8"	T8	8" Torquer		

\*Size will also fit Sched. 80 pipe



**Koby Environmental**  
Manufacturers of Environmental Groundwater Testing Equipment